## 860

## Purchase Order Change Request - Buyer Initiated

- 1. Change Orders will be accepted by VANTAGE GROUP® via EDI 860 Document. Because of the complexity of handling Change orders they will be converted by VANTAGE GROUP® to paper and faxed or E-mailed to the local servicing branch.
- 2. If a confirmation is required for the Change order this will be handled through a manual process.

•

<u>Pos</u>	<u>Id</u>	Segment Name	Req	Max Use	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control	M	1			Must Use
		Header					
	GS	Functional Group Header	M	1			Must Use
Head	ing:						
<u>Pos</u>	<u>Id</u>	Segment Name	Req	Max Use	Repeat	<u>Notes</u>	<u>Usage</u>
10	ST	Transaction Set Header	M	1			Must Use
20	BCH	<b>Beginning Segment for</b>	M	1			Must Use
		Purchase Order Change					
40	CUR	Currency	0	1			Used
50	REF	Reference Identification	0	>1			Used
60	PER	Administrative	0	3			Used
		Communications					
		Contact					
150	DTM	Date/Time Reference	0	10			Used
LOOP	ID_N9				1000		
285	N9	Reference	0	1			Used
		Identification					
290	MSG	Message Text	0	1000			Used
LOOP	ID_N1				200		
300	N1	Name	0	1			Used
320	N3	Address Information	0	2			Used
330	N4	Geographic Location	0	>1			Used

#### **Detail:**

<u>Pos</u>	<u>Id</u>	Segment Name	Req	Max Use	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP	ID_PO	С			>1		
10	POC	Line Item Change	0	1			Used
40	CTP	<b>Pricing Information</b>	0	>1			Used
LOOP ID _ PID					1000		

#### VANTAGE GROUP® 860 Purchase Order Change Request

50	PID	Product/Item	0	1	Used
		Description			
100	REF	Reference	0	>1	Used
		Identification			
180	FOB	F.O.B. Related	0	>1	Used
		Instructions			
200	DTM	Date/Time Reference	0	10	Used
LOOP	ID_N9			1000	
320	N9	Reference	0	1	Used
		Identification			
330	MSG	Message Text	0	1000	Used

#### **Summary:**

<u>Pos</u>	<u>Id</u>	Segment Name	Req	Max Use	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOF	D_C	ГТ			1		
10	CTT	<b>Transaction Totals</b>	0	1			Used
30	SE	Transaction Set Trailer	M	1			Must Use
Not [	Define:						
	GE	Functional Group Header	M	1			Must Use
	IEA	Interchange Control Trailer	М	1			Must Use

## **ISA** Interchange Control Header

Pos: Max: 1
Not Defined - Mandatory
Loop: N/A Elements: 16

Licincii	•					
<u>Ref</u> ISA01	<u>Id</u> 101	<u>Element Name</u> Authorization Information Qualifier	<u>Req</u> M	<u>Type</u> ID	<u>Min/Max</u> 2/2	<u>Usage</u> Must use
		Description:				
ISA02	102	Authorization Information  Description:	M	AN	10/10	Must use
ISA03	103	Security Information Qualifier	М	ID	2/2	Must use
		Description:				
ISA04	104	Security Information	М	AN	10/10	Must use
13AU4	104	Description:	IVI	AIN	10/10	wiust use
ISA05	105	Interchange Sender ID Qualifier	M	ID	2/2	Must use
		Description:				
ISA06	106	Interchange Sender ID	M	AN	15/15	Must use
ISAUU	100	Description:	IVI	AIN	13/13	wiust use
ISA07	107	Interchange Receiver ID	M	ID	2/2	Must use
		Qualifier				
		Description:			4	
ISA08	108	Interchange Receiver ID  Description:	M	AN	15/15	Must use
ISA09	109	Interchange Date	M	DT	6/6	Must use
		Description:			•	
ISA10	I10	Interchange Time	M	TM	4/4	Must use
		Description:				
ISA11	l11	Interchange Control Standards Identifier	M	ID	1/1	Must use
		Description:				
ISA12	l12	Interchange Control	М	ID	5/5	Must use
		Version Number			-,-	
		Description:				
ISA13	I13	Interchange Control	M	N0	9/9	Must use
		Number				
ISA14	l14	<b>Description:</b> Acknowledgment	M	ID	1/1	Must use
		Requested	•••		-, <del>-</del>	
		Description:				
ISA15	l15	Usage Indicator	M	ID	1/1	Must use

#### VANTAGE GROUP® 860 Purchase Order Change Request

**Description:** 

ISA16 I16 Component Element M 1/1 Must use

Separato **Description:** 

## **GS** Functional Group Header

Pos: Max: 1
Not Defined - Mandatory
Loop: N/A Elements: 8

#### Used

Ref	<u>Id</u>	Element Name	Req	<u>Type</u>	Min/Max	<u>Usage</u>
GS01	GS01	Functional Identifier	M	ID	2/2	Must use
		Coder				
		Description:				
GS02	GS02	Application Sender's Code	M	AN	2/15	Must use
		Description:				
GS03	GS03	Application Receiver's	M	AN	2/15	Must use
		Code				
		Description:				
GS04	GS04	Date	M	DT	8/8	Must use
		Description:				
GS05	GS05	Time	M	TM	4/8	Must use
		Description:				
GS06	GS06	Group Control Number	M	N0	1/9	Must use
		Description:				
GS07	GS07	Responsible Agency Code	M	ID	1/2	Must use
		Description:				
GS08	GS08	Version / Release /	M	AN	1/12	Must use
		Industry Identifier Code				
		Description:				

## Transaction Set Header

Pos: 10 Max: 1
Header - Mandatory
Loop: N/A Elements: 2

#### Used

Ref	<u>Id</u>	<b>Element Name</b>	Req	<u>Type</u>	Min/Max	<u>Usage</u>
ST001	143	Transaction Set Identifier	M/Z	ID	3/3	Used
		Code				
		Description:				
ST002	329	<b>Transaction Set Control</b>	M	AN	4/9	Must use
		Number				
		Description:				

<sup>\*</sup>See ASC X12 Nomenclature, to review the transaction set structure, including descriptions of segments, data elements, levels, and loops

## **BCH** Beginning Segment for Purchase Order Change

Pos: 20 Max: 1
Header - Mandatory
Loop: N/A Elements: 4

#### Used

Ref	<u>Id</u> ,	Element Name	<u>Req</u>	<u>Type</u>	Min/Max	<u>Usage</u>
BCH001	353	Transaction Set Purpose	M	ID	2/2	Must use
		Code				
		Description:				
BCH002	92	Purchase Order Type Code	M	ID	2/2	Must use
		Description:				
BCH003	324	Purchase Order Number	M	AN	1/22	Must use
		Description:				
BCH006	373	Date	M/Z	DT	8/8	Used
		Description:				

**CUR** Currency

Pos: 40 Max: 1
Header - Optional
Loop: N/A Elements: 2

Used

<u>Ref</u>	<u>Id</u>	Element Name	Req	<u>Type</u>	Min/Max	<u>Usage</u>
CUR001	98	Entity Identifier Code	M	ID	2/3	Must use
		Description:				
CUR002	100	Currency Code	M	ID	3/3	Must use
		Description:				

## **REF** Reference Identification

Pos: 50 Max: >1
Header - Optional
Loop: N/A Elements: 2

Used

Ref	<u>Id</u>	<b>Element Name</b>	Req	<u>Type</u>	Min/Max	<u>Usage</u>
REF001	128	Reference Identification Qualifier Description:	M	ID	2/3	Must use
REF002	127	Reference Identification <b>Description:</b>	X	AN	1/30	Used

# PER Administrative Communications Contact

Pos: 60 Max: 3
Header - Optional
Loop: N/A Elements: 8

#### Used

<u>Ref</u>	<u>Id</u>	<b>Element Name</b>	<u>Req</u>	<u>Type</u>	Min/Max	<u>Usage</u>
PERO01	366	Contact Function Code	M	ID	2/2	Must use
		Code Purpose				
		BD Buyer Name or De	partment			
		Description:				
PERO02	93	Name	0	AN	1/60	Used
		Description:				
PER003	365	Communication Number Qualifier	Χ	ID	2/2	Used
		Code Purpose				
		EM Electronic Mail				
		TE Telephone				
		FX Facsimile				
		Description:				
PERO04	364	Communication Number	Χ	AN	1/80	Used
		Description:				
PERO05	365	Communication Number	Χ	ID	2/2	Used
		Qualifier				
		Description:				
PER006	364	Communication Number	Χ	AN	1/80	Used
		Description:				
PERO07	365	Communication Number	Χ	ID	2/2	Used
		Qualifier				
		Description:				
PER008	364	Communication Number	Χ	AN	1/80	Used
		Description:				

## **DTM** Date/Time Reference

Pos: 150 Max: 10
Header - Optional
Loop: N/A Elements: 2

Used

Ref	<u>Id</u>	Element Name	<u>Req</u>	<u>Type</u>	Min/Max	<u>Usage</u>
DTM001	374	Date/Time Qualifier	M	ID	3/3	Must use
		Description:				
DTM002	373	Date	Χ	DT	8/8	Used
		Description:				

## **N9** Reference Identification

Pos: 285 Max: 1
Header - Optional
Loop: N9 Elements: 3

Ref	<u>Id</u>	<b>Element Name</b>	<u>Req</u>	<u>Type</u>	Min/Max	<b>Usage</b>
N9001	128	Reference Identification Qualifier Description:	М	ID	2/3	Must use
N9002	127	Reference Identification <b>Description:</b>	X	AN	1/30	Used
N9003	369	Free-form Description  Description:	Χ	AN	1/45	Used

**MSG** Message Text

Pos: 290 Max: 1000 Header - Optional Loop: N9 Elements: 1

Used

**Element Summary:** 

RefIdElement NameReqTypeMin/MaxUsageMSG001933Free-Form Message TextMAN1/264Must use

**Description:** 

N1 Name

Pos: 300 Max: 1
Header - Optional
Loop: N1 Elements: 4

Licincii	<b>5</b> a ,	Element Sammary.							
Ref	<u>Id</u>	<b>Element Name</b>	<u>Req</u>	<u>Type</u>	Min/Max	<u>Usage</u>			
N1001	98	<b>Entity Identifier Code</b>	M	ID	2/3	Must use			
		Description:							
N1002	93	Name	Χ	AN	1/60	Used			
		Description:							
N1003	66	Identification Code	Χ	ID	1/2	Used			
		Qualifier							
		Description:							
N1004	67	Identification Code	Χ	AN	2/80	Used			
		Description:							

## **N3** Address Information

Pos: 320 Max: 2
Header - Optional
Loop: N1 Elements: 2

Ref	<u>Id</u>	<b>Element Name</b>	Req	<u>Type</u>	Min/Max	<u>Usage</u>
N3001	166	Address Information	M	AN	1/55	Must use
		Description:				
N3002	166	Address Information	0	AN	1/55	Used
		Description:				

### **N4**

## **Geographic Location**

Pos: 330 Max: >1
Header - Optional
Loop: N1 Elements: 4

Ref	<u>Id</u>	Element Name	<u>Req</u>	<u>Type</u>	Min/Max	Usage
N4001	19	City Name	0	AN	2/30	Used
		Description:				
N4002	156	State or Province Code	0	ID	2/2	Used
		Description:				
N4003	116	Postal Code	0	ID	3/15	Used
		Description:				
N4004	26	Country Code	0	ID	2/3	Used
		Description:				

## **POC** Line Item Change

Pos: 10 Max: 1
Detail - Optional
Loop: POC Elements: 28

Licinciic	aiiiiiiai y	•				
<u>Ref</u> POC001	<u>Id</u> 350	Element Name	<u><b>Req</b></u> O/Z	<u>Type</u> AN	Min/Max 1/20	<u>Usage</u> Used
POC001	330	Assigned Identification  Description:	0/2	AIN	1/20	oseu
POC002	670	Change or Response Type	M	ID	2/2	Must use
		Code				
		Description:				
POC003	330	Quantity Ordered	0	RD	1/15	Used
	c=4	Description:	.,		. /0	
POC004	671	Quantity Left to Receive <b>Description:</b>	X	RD	1/9	Used
POC005	C001	Composite Unit of	Х			Used
	0001	Measure	,			<b>3</b> 3 3 4
		Description:				
POC005-	355	Unit or Basis for	M	ID	2/2	Must use
1		Measurement Code				
		Description:				
POC006	212	Unit Price	X	RD	1/17	Used
		Description:				_
POC007	639	Basis of Unit Price Code	0	ID	2/2	Used
POC008	235	<b>Description:</b> Product/Service ID	Χ	ID	2/2	Used
PUC008	233	Qualifier	^	וט	2/2	Oseu
		Description:				
POC009	234	Product/Service ID	Χ	AN	1/48	Used
		Description:				
POC10	235	Product/Service ID	Χ	ID	2/2	Used
		Qualifier				
		Description:				
POC11	234	Product/Service ID	X	AN	1/48	Used
POC12	225	Description:	V	ID	2/2	Used
PUC12	235	Product/Service ID Qualifier	X	ID	2/2	usea
		Description:				
POC13	234	Product/Service ID	X	AN	1/48	Used
		Description:			_,	
POC14	235	Product/Service ID	Χ	ID	2/2	Used
		Qualifier				
		Description:				
POC15	234	Product/Service ID	X	AN	1/48	Used

#### VANTAGE GROUP® 860 Purchase Order Change Request

POC16	235	<b>Description:</b> Product/Service ID	X	ID	2/2	Used
		Qualifier  Description:				
POC17	234	Product/Service ID  Description:	Χ	AN	1/48	Used
POC18	235	Product/Service ID Qualifier Description:	X	ID	2/2	Used
POC19	234	Product/Service ID  Description:	Х	AN	1/48	Used
POC20	235	Product/Service ID Qualifier <b>Description:</b>	X	ID	2/2	Used
POC21	234	Product/Service ID  Description:	Χ	AN	1/48	Used
POC22	235	Product/Service ID Qualifier Description:	Х	ID	2/2	Used
POC23	234	Product/Service ID  Description:	Χ	AN	1/48	Used
POC24	235	Product/Service ID Qualifier Description:	X	ID	2/2	Used
POC25	234	Product/Service ID  Description:	Χ	AN	1/48	Used
POC26	235	Product/Service ID Qualifier Description:	X	ID	2/2	Used
POC27	234	Product/Service ID  Description:	Х	AN	1/48	Used

## **CTP** Pricing Information

Pos: 40 Max: >1
Detail - Optional
Loop: POC Elements: 12

<u>Ref</u>	<u>Id</u>	Element Name	Req	Type	Min/Max	<u>Usage</u>
CTP001	687	Class of Trade Code  Description:	0	ID	2/2	Used
CTP002	236	Price Identifier Code	X	ID	3/3	Used
CTP003	212	<b>Description:</b> Unit Price	X	RD	1/17	Used
CTP004	380	<b>Description:</b> Quantity	X	RD	1/15	Used
C17004	360	Description:	^	ND	1/13	oseu
CTP005	C001	Composite Unit of Measure	Χ			Used
		Description:				
CTP005-	355	Unit or Basis for	M	ID	2/2	Must use
1		Measurement Code  Description:				
CTP006	648	Price Multiplier Qualifier <b>Description:</b>	0	ID	3/3	Used
CTP007	649	Multiplier	X/Z	RD	1/10	Used
CTDOOG	702	Description:	0/7	DD	1 /10	Head
CTP008	782	Monetary Amount  Description:	O/Z	RD	1/18	Used
CTP009	639	Basis of Unit Price Code	0	ID	2/2	Used
CTP10	499	<b>Description:</b> Condition Value	0	AN	1/10	Used
		Description:				
CTP11	289	Multiple Price Quantity  Description:	0	N0	1/2	Used

## PID Product/Item Description

Pos: 50 Max: 1
Detail - Optional
Loop: PID Elements: 9

Elelliell	t Sullillial	y.				
<u>Ref</u>	<u>Id</u>	Element Name	<u>Req</u>	<u>Type</u>	Min/Max	<u>Usage</u>
PID001	349	Item Description Type  Description:	M	ID	1/1	Must use
PID002	750	Product/Process	0	ID	2/3	Used
		Characteristic Code  Description:				
PID003	559	Agency Qualifier Code	X/Z	ID	2/2	Used
		Description:				
PID004	751	Product Description Code	X/Z	AN	1/12	Used
		Description:				
PID005	352	Description	X	AN	1/80	Used
		Description:				
PID006	752	Surface/Layer/Position	0	ID	2/2	Used
		Code				
		Description:				
PID007	822	Source Subqualifier	0	AN	1/15	Used
		Description:				
PID008	1073	Yes/No Condition or	O/Z	ID	1/1	Used
		Response Code				
		Description:				
PID009	819	Language Code	O/Z	ID	2/3	Used
		Description:				

## **REF** Reference Identification

Pos: 100 Max: >1
Detail - Optional
Loop: POC Elements: 3

Ref	<u>. Id</u>	<b>Element Name</b>	Req	<u>Type</u>	Min/Max	<u>Usage</u>
REF001	128	Reference Identification Qualifier Description:	M	ID	2/3	Must use
REF002	127	Reference Identification  Description:	X	AN	1/30	Used
REF003	352	Description  Description:	Χ	AN	1/80	Used

## **FOB** F.O.B. Related Instructions

Pos: 180 Max: >1
Detail - Optional
Loop: POC Elements: 1

Used

**Element Summary:** 

RefIdElement NameReqTypeMin/MaxUsageFOB001146Shipment Method ofM/ZID2/2Used

Payment **Description:** 

## **DTM** Date/Time Reference

Pos: 200 Max: 10
Detail - Optional
Loop: POC Elements: 2

Used

<u>Ref</u>	<u>Id</u>	Element Name	Req	<u>Type</u>	Min/Max	<u>Usage</u>
DTM001	374	Date/Time Qualifier	M	ID	3/3	Must use
		Description:				
DTM002	373	Date	Χ	DT	8/8	Used
		Description:				

## **N9** Reference Identification

Pos: 320 Max: 1
Detail - Optional
Loop: N9 Elements: 6

Ref	<u>. Id</u>	Element Name	Req	Type	Min/Max	<u>Usage</u>
N9001	128	Reference Identification	M	ID	2/3	Must use
		Qualifier				
		Description:				
N9002	127	Reference Identification	Χ	AN	1/30	Used
		Description:				
N9003	369	Free-form Description	Χ	AN	1/45	Used
		Description:				
N9004	373	Date	0	DT	8/8	Used
		Description:				
N9005	337	Time	Χ	TM	4/8	Used
		Description:				
N9006	623	Time Code	O/Z	ID	2/2	Used
		Description:				

**MSG** Message Text

Pos: 330 Max: 1000 Detail - Optional Loop: N9 Elements: 1

Used

**Element Summary:** 

RefIdElement NameReqTypeMin/MaxUsageMSG001933Free-Form Message TextMAN1/264Must use

**Description:** 

**CTT** 

### **Transaction Totals**

Pos: 10 Max: 1
Summary - Optional
Loop: CTT Elements: 1

Used

**Element Summary:** 

RefIdElement NameReqTypeMin/MaxUsageCTT001354Number of Line ItemsMN01/6Must use

**Description:** 

**SE** Transaction Set Trailer

Pos: 30 Max: 1
Summary - Mandatory
Loop: N/A Elements: 2

Used

Ref	<u>Id</u>	<b>Element Name</b>	<u>Req</u>	<u>Type</u>	Min/Max	<u>Usage</u>
SE001	96	Number of Included	M	N0	1/10	Must use
		Segments				
		Description:				
SE002	329	Transaction Set Control	M	AN	4/9	Must use
		Number				
		Description:				

## **GE** Functional Group Header

Pos: Max: 1
Not Defined - Mandatory
Loop: N/A Elements: 2

#### Used

Ref	<u>Id</u>	<b>Element Name</b>	<u>Req</u>	<u>Type</u>	Min/Max	<u>Usage</u>
GE01	GE01	Number of Transaction Sets Included Description:	М	N0	1/6	Must use
GE02	GE02	Group Control Number  Description:	М	N0	1/9	Must use

## **IEA** Interchange Control Trailer

Pos: Max: 1
Not Defined - Mandatory
Loop: N/A Elements: 2

#### Used

Ref	<u>Id</u>	<b>Element Name</b>	<u>Req</u>	<u>Type</u>	Min/Max	<u>Usage</u>
IEA01	IEA01	Number of Included Functional Groups <b>Description:</b>	M	NO	1/5	Must use
IEA02	IEA02	Interchange Control Number Description:	М	N0	9/9	Must use

# ASC X12 Nomenclature Interchange and Application Control Structures Interchange Control Structure




Figure A1. Transmission Control Schematic

The transmission of data proceeds according to very strict format rules to ensure the integrity and maintain the efficiency of the interchange. Each business grouping of data is called a transaction set. For instance, a group of benefit enrollments sent from a sponsor to a payer is considered a transaction set. Each transaction set contains groups of logically related data in units called segments. For instance, the N4 segment used in the transaction set conveys the city, state, ZIP Code, and other geographic information. A transaction set contains multiple segments, so the addresses of the different parties, for example, can be conveyed from one computer to the other. An analogy would be that the transaction set is like a freight train; the segments are like the train's cars; and each segment can contain several

data elements the same as a train car can hold multiple crates. The sequence of the elements within one segment is specified by the ASC X12 standard as well as the sequence of segments in the transaction set. In a more conventional computing environment, the segments would be equivalent to records, and the elements equivalent to fields. Similar transaction sets, called "functional groups," can be sent together within a transmission. Each functional group is prefaced by a group start segment; and a functional group is terminated by a group end segment. One or more functional groups are prefaced by an interchange header and followed by an interchange trailer. Figure A1, Transmission Control Schematic, illustrates this interchange control. The interchange header and trailer segments envelop one or more functional groups or interchange-related control segments and perform the following functions:

- 1. Define the data element separators and the data segment terminator.
- 2. Identify the sender and receiver.
- 3. Provide control information for the interchange.
- 4. Allow for authorization and security information.

## **Application Control Structure Definitions and Concepts Basic Structure**

A data element corresponds to a data field in data processing terminology. The data element is the smallest named item in the ASC X12 standard. A data segment corresponds to a record in data processing terminology. The data segment begins with a segment ID and contains related data elements. A control segment has the same structure as a data segment; the distinction is in the use. The data segment is used primarily to convey user information, but the control segment is used primarily to convey control information and to group data segments.

#### **Basic Character Set**

AZ	09	!	**	&	,	(	)	*	+
,		1120	1	:	;	?	=	" " (s	pace)

Figure A2. Basic Character Set

The section that follows is designed to have representation in the common character code schemes of EBCDIC, ASCII, and CCITT International Alphabet 5. The ASC X12 standards are graphic-character-oriented; therefore, common character encoding schemes other than those specified herein may be used as long as a common mapping is available. Because the graphic characters have an implied mapping across character code schemes, those bit patterns are not provided here.

The basic character set of this standard, shown in figure A2, Basic Character Set, includes those selected from the uppercase letters, digits, space, and special characters as specified below.

#### **Extended Character Set**

az	%	~	@	1	]	_	{
}	1	1	<	>	#	\$	

Figure A3. Extended Character Set

An extended character set may be used by negotiation between the two parties and includes the lowercase letters and other special characters as specified in figure A3, Extended Character Set. Note that the extended characters include several character codes that have multiple graphical representations for a specific bit pattern. The complete list appears in other standards such as CCITT S.5.

Use of the USA graphics for these codes presents no problem unless data is exchanged with an international partner. Other problems, such as the translation of item descriptions from English to French, arise when exchanging data with an international partner, but minimizing the use of codes with multiple graphics eliminates one of the more obvious problems.

#### **Control Characters**

Two control character groups are specified; they have only restricted usage. The common notation for these groups is also provided, together with the character coding in three common alphabets. In the matrix A1, Base Control Set, the column IA5 represents CCITT V.3 International Alphabet 5.

#### **Base Control Set**

NAME	EBCDIC	ASCII	IA5
bell	2F	07	07
horizontal tab	05	09	09
line feed	25	0A	0A
vertical tab	0B	0B	0B
form feed	0C	0C	0C
carriage return	0D	0D	0D
file separator	1C	1C	1C
group separator	1D	1D	1D
record separator	1E	1E	1E
unit separator	1F	1F	1F
new line	15	Const.	
	bell horizontal tab line feed vertical tab form feed carriage return file separator group separator record separator unit separator	bell 2F horizontal tab 05 line feed 25 vertical tab 0B form feed 0C carriage return 0D file separator 1C group separator 1D record separator 1E unit separator 1F	bell         2F         07           horizontal tab         05         09           line feed         25         0A           vertical tab         0B         0B           form feed         0C         0C           carriage return         0D         0D           file separator         1C         1C           group separator         1D         1D           record separator         1E         1E           unit separator         1F         1F

#### Matrix A1. Base Control Set

The base control set includes those characters that will not have a disruptive effect on most communication protocols. These are represented by: The Group Separator (GS) may be an exception in this set because it is used in the 3780 communications protocol to indicate blank space compression.

#### **Extended Control Set**

NOTATION	NAME	EBCDIC	ASCII	IA5
SOH	start of header	01	01	01
STX	start of text	02	02	02
ETX	end of text	03	03	03
EOT	end of transmission	37	04	04
ENQ	enquiry	2D	05	05
ACK	acknowledge	2E	06	06
DC1	device control 1	11	11	11
DC2	device control 2	12	12	12
DC3	device control 3	13	13	13
DC4	device control 4	3C	14	14
NAK	negative acknowledge	3D	15	15
SYN	synchronous idle	32	16	16
ETB	end of block	26	17	17

#### Matrix A2. Extended Control Set

The extended control set includes those that may have an effect on a transmission system. These are shown in matrix A2, Extended Control Set.

#### **Delimiters**

NAME	DELIMITER		
Asterisk	Data Element Separate		
Colon	Subelement Separator		
Tilde	Segment Terminator		
	Asterisk Colon		

#### Matrix A3. Delimiters

A delimiter is a character used to separate two data elements (or subelements) or to terminate a segment. The delimiters are an integral part of the data.

Delimiters are specified in the interchange header segment, ISA. The ISA segment is a 105 byte fixed length record. The data element separator is byte number 4; the component element separator is byte number 105; and the segment terminator is the byte that immediately follows the component element separator. Once specified in the interchange header, the delimiters are not to be used in a data element value elsewhere in the interchange. For consistency, this implementation guide uses the delimiters shown in matrix A3, Delimiters, in all examples of EDI transmissions.

The delimiters above are for illustration purposes only and are not specific recommendations or requirements. Users of this implementation guide should be aware that an application system may use some valid delimiter characters within the application data. Occurrences of delimiter characters in transmitted data within a data element can result in errors in translation programs. The existence of asterisks (\*) within transmitted application data is a known issue that can affect translation software.

#### **Business Transaction Structure Definitions and Concepts**

The ASC X12 standards define commonly used business transactions (such as a health care claim) in a formal structure called "transaction sets." A transaction set is composed of a transaction set header control segment, one or more data segments, and a transaction set trailer control segment. Each

segment is composed of the following:

- · A unique segment ID
- · One or more logically related data elements each preceded by a data element separator
- · A segment terminator

#### **Data Element**

TYPE
Numeric
Decimal
Identifier
String
Date
Time
Binary

#### Matrix A4. Data Element Types

The data element is the smallest named unit of information in the ASC X12 standard. Data elements are identified as either simple or component. A data element that occurs as an ordinarily positioned member of a composite data structure is identified as a component data element. A data element that occurs in a segment outside the defined boundaries of a composite data structure is identified as a simple data element. The distinction between simple and component data elements is strictly a matter of context because a data element can be used in either capacity.

Data elements are assigned a unique reference number. Each data element has a name, description, type, minimum length, and maximum length. For ID type data elements, this guide provides the applicable ASC X12 code values and their descriptions or references where the valid code list can be obtained. Each data element is assigned a minimum and maximum length. The length of the data element value is the number of character positions used except as noted for numeric, decimal, and binary elements.

The data element types shown in matrix A4, Data Element Types, appear in this implementation guide.

#### Numeric

A numeric data element is represented by one or more digits with an optional leading sign representing a value in the normal base of 10. The value of a numeric data element includes an implied decimal point. It is used when the position of the decimal point within the data is permanently fixed and is not to be transmitted with the data.

This set of guides denotes the number of implied decimal positions. The representation for this data element type is "Nn" where N indicates that it is numeric and n indicates the number of decimal positions to the right of the implied decimal point.

If n is 0, it need not appear in the specification; N is equivalent to N0. For negative values, the leading minus sign (-) is used. Absence of a sign indicates a positive value. The plus sign (+) should not be transmitted.

#### **EXAMPLE**

A transmitted value of 1234, when specified as numeric type N2, represents a value of 12.34. Leading zeros should be suppressed unless necessary to satisfy a minimum length requirement. The length of a numeric type data element does not include the optional sign.

#### Decimal

A decimal data element may contain an explicit decimal point and is used for numeric values that have a varying number of decimal positions. This data element type is represented as "R."

The decimal point always appears in the character stream if the decimal point is at any place other than the right end. If the value is an integer (decimal point at the right end) the decimal point should be omitted. For negative values, the leading minus sign (-) is used. Absence of a sign indicates a positive value. The plus sign (+) should not be transmitted.

Leading zeros should be suppressed unless necessary to satisfy a minimum length requirement. Trailing zeros following the decimal point should be suppressed unless necessary to indicate precision. The use of triad separators (for example, the commas in 1,000,000) is expressly prohibited. The length of a decimal type data element does not include the optional leading sign or decimal point.

A transmitted value of 12.34 represents a decimal value of 12.34.

#### **Identifier**

**EXAMPLE** 

An identifier data element always contains a value from a predefined list of codes that is maintained by the ASC X12 Committee or some other body recognized by the Committee. Trailing spaces should be suppressed unless they are necessary to satisfy a minimum length. An identifier is always left justified. The representation for this data element type is "ID."

#### String

A string data element is a sequence of any characters from the basic or extended character sets. The significant characters shall be left justified. Leading spaces, when they occur, are presumed to be significant characters. Trailing spaces should be suppressed unless they are necessary to satisfy a minimum length. The representation for this data element type is "AN."

#### **Date**

A date data element is used to express the standard date in either YYMMDD or CCYYMMDD format in which CC is the first two digits of the calendar year, YY is the last two digits of the calendar year, MM is the month (01 to 12), and DD is the day in the month (01 to 31). The representation for this data element type is "DT." Users of this guide should note that all dates within transactions are 8-character dates (millennium compliant) in the format CCYYMMDD. The only date data element that is in format YYMMDD is the Interchange Date data element in the ISA segment, and also used in the TA1 Interchange Acknowledgment, where the century can be readily interpolated because of the nature of an interchange header.

#### Time

A time data element is used to express the ISO standard time HHMMSSd..d format in which HH is the hour for a 24 hour clock (00 to 23), MM is the minute (00 to 59), SS is the second (00 to 59) and d..d is decimal seconds. The representation for this data element type is "TM." The length of the data element determines the format of the transmitted time.

#### **EXAMPLE**

Transmitted data elements of four characters denote HHMM. Transmitted data elements of six characters denote HHMMSS.

#### **Composite Data Structure**

The composite data structure is an intermediate unit of information in a segment. Composite data structures are composed of one or more logically related simple data elements, each, except the last, followed by a sub-element separator. The final data element is followed by the next data element separator or the segment terminator. Each simple data element within a composite is called a component. Each composite data structure has a unique four-character identifier, a name, and a

purpose. The identifier serves as a label for the composite. A composite data structure can be further defined through the use of syntax notes, semantic notes, and comments. Each component within the composite is further characterized by a reference designator and a condition designator. The reference designators and the condition designators are described below.

#### **Data Segment**

The data segment is an intermediate unit of information in a transaction set. In the data stream, a data segment consists of a segment identifier, one or more composite data structures or simple data elements each preceded by a data element separator and succeeded by a segment terminator. Each data segment has a unique two- or three-character identifier, a name, and a purpose. The identifier serves as a label for the data segment. A segment can be further defined through the use of syntax notes, semantic notes, and comments. Each simple data element or composite data structure within the segment is further characterized by a reference designator and a condition designator.

#### **Syntax Notes**

Syntax notes describe relational conditions among two or more data segment units within the same segment, or among two or more component data elements within the same composite data structure.

#### Semantic Notes

Simple data elements or composite data structures may be referenced by a semantic note within a particular segment. A semantic note provides important additional information regarding the intended meaning of a designated data element, particularly a generic type, in the context of its use within a specific data segment. Semantic notes may also define a relational condition among data elements in a segment based on the presence of a specific value (or one of a set of values) in one of the data elements.

#### Comments

A segment comment provides additional information regarding the intended use of the segment.

#### **Reference Designator**

Each simple data element or composite data structure in a segment is provided a structured code that indicates the segment in which it is used and the sequential position within the segment. The code is composed of the segment identifier followed by a two-digit number that defines the position of the simple data element or composite data structure in that segment.

For purposes of creating reference designators, the composite data structure is viewed as the hierarchical equal of the simple data element. Each component data element in a composite data structure is identified by a suffix appended to the reference designator for the composite data structure of which it is a member. This suffix is a two-digit number, prefixed with a hyphen, that defines the position of the component data element in the composite data structure.

#### **EXAMPLE**

- $\cdot$  The first simple element of the CLP segment would be identified as CLP01.
- The first position in the SVC segment is occupied by a composite data structure that contains seven component data elements, the reference designator for the second component data element would be SVC01-02.

#### **Condition Designator**

This section provides information about X12 standard conditions designators. It is provided so that users will have information about the general standard. Implementation guides may impose other conditions designators.

Data element conditions are of three types: mandatory, optional, and relational. They define the

circumstances under which a data element may be required to be present or not present in a particular segment.

DESIGNATOR	DESCRIPTION					
M- Mandatory	The designation of man	datory is absolute in the sense that there is no				
•	dependency on other data elements. This designation may apply to either					
	simple data elements or	r composite data structures. If the designation applies				
	to a composite data stru	ucture, then at least one value of a component data				
	element in that compos	site data structure shall be included in the data				
	segment.					
O- Optional	The designation of optic	onal means that there is no requirement for a simple				
	data element or compos	site data structure to be present in the segment. The				
		a simple data element or the presence of value for any				
	-	elements of a composite data structure is at the				
	option of the sender.	·				
X- Relational	Relational conditions ma	ay exist among two or more simple data elements				
	within the same data se	gment based on the presence or absence of one of				
	those data elements (pr	resence means a data element must not be empty).				
		e specified by a condition code (see table below) and				
		ors of the affected data elements. A data element may				
	be subject to more than	one relational condition. The definitions for each of				
	the condition codes used within syntax notes are detailed below:					
	<b>CONDITION CODE</b>	DEFINITION				
	P- Paired or Multiple	If any element specified in the relational condition is				
		present, then all of the elements specified must be				
		present.				
	R- Required	At least one of the elements specified in the				
	·	condition must be present.				
	E- Exclusion	Not more than one of the elements specified in the				
		condition may be present.				
	C- Conditional	If the first element specified in the condition is				
		present, then all other elements must be present.				
		However, any or all of the elements not specified as				
		the first element in the condition may appear				
		without requiring that the first element be present.				
		The order of the elements in the condition does not				
		have to be the same as the order of the data				
		elements in the data segment.				
	L- List Conditional	If the first element specified in the condition is				
		present, then at least one of the remaining elements				
		must be present. However, any or all of the elements				
		not specified as the first element in the condition				
		may appear without requiring that the first element				
		be present. The order of the elements in the				
		condition does not have to be the same as the order				
		of the data elements in the data segment.				
Control Coamonto						

#### **Control Segments**

A control segment has the same structure as a data segment, but it is used for transferring control information rather than application information.

#### **Loop Control Segments**

Loop control segments are used only to delineate bounded loops. Delineation of the loop shall consist of the loop header (LS segment) and the loop trailer (LE segment). The loop header defines the start of a structure that must contain one or more iterations of a loop of data segments and provides the loop identifier for this loop. The loop trailer defines the end of the structure. The LS segment appears only before the first occurrence of the loop, and the LE segment appears only after the last occurrence of the loop. Unbounded looping structures do not use loop control segments.

#### **Transaction Set Control Segments**

The transaction set is delineated by the transaction set header (ST segment) and the transaction set trailer (SE segment). The transaction set header identifies the start and identifier of the transaction set. The transaction set trailer identifies the end of the transaction set and provides a count of the data segments, which includes the ST and SE segments.

#### **Functional Group Control Segments**

The functional group is delineated by the functional group header (GS segment) and the functional group trailer (GE segment). The functional group header starts and identifies one or more related transaction sets and provides a control number and application identification information. The functional group trailer defines the end of the functional group of related transaction sets and provides a count of contained transaction sets.

#### **Relations among Control Segments**

The control segment of this standard must have a nested relationship as is shown and annotated in this subsection. The letters preceding the control segment name are the segment identifier for that control segment. The indentation of segment identifiers shown below indicates the subordination among control segments.

GS Functional Group Header, starts a group of related transaction sets.

ST Transaction Set Header, starts a transaction set.

LS Loop Header, starts a bounded loop of data segments but is not part of the loop.

LS Loop Header, starts an inner, nested, bounded loop.

LE Loop Trailer, ends an inner, nested bounded loop.

LE Loop Trailer, ends a bounded loop of data segments but is not part of the loop.

SE Transaction Set Trailer, ends a transaction set.

GE Functional Group Trailer, ends a group of related transaction sets.

More than one ST/SE pair, each representing a transaction set, may be used within one functional group. Also more than one LS/LE pair, each representing a bounded loop, may be used within one transaction set.

#### **Transaction Set**

The transaction set is the smallest meaningful set of information exchanged between trading partners. The transaction set consists of a transaction set header segment, one or more data segments in a specified order, and a transaction set trailer segment. See figure A1, Transmission Control Schematic.

#### **Transaction Set Header and Trailer**

A transaction set identifier uniquely identifies a transaction set. This identifier is the first data element of the Transaction Set Header Segment (ST). A user assigned transaction set control number in the header must match the control number in the Trailer Segment (SE) for any given transaction set. The value for the number of included segments in the SE segment is the total number of segments in the

transaction set, including the ST and SE segments.

#### **Data Segment Groups**

The data segments in a transaction set may be repeated as individual data segments or as unbounded or bounded loops.

#### **Repeated Occurrences of Single Data Segments**

When a single data segment is allowed to be repeated, it may have a specified maximum number of occurrences defined at each specified position within a given transaction set standard. Alternatively, a segment may be allowed to repeat an unlimited number of times. The notation for an unlimited number of repetitions is ">1."

#### **Loops of Data Segments**

Loops are groups of semantically related segments. Data segment loops may be unbounded or bounded.

#### **Unbounded Loops**

To establish the iteration of a loop, the first data segment in the loop must appear once and only once in each iteration. Loops may have a specified maximum number of repetitions. Alternatively, the loop may be specified as having an unlimited number of iterations. The notation for an unlimited number of repetitions is ">1."

A specified sequence of segments is in the loop. Loops themselves are optional or mandatory. The requirement designator of the beginning segment of a loop indicates whether at least one occurrence of the loop is required. Each appearance of the beginning segment defines an occurrence of the loop. The requirement designator of any segment within the loop after the beginning segment applies to that segment for each occurrence of the loop. If there is a mandatory requirement designator for any data segment within the loop after the beginning segment, that data segment is mandatory for each occurrence of the loop. If the loop is optional, the mandatory segment only occurs if the loop occurs.

#### **Bounded Loops**

The characteristics of unbounded loops described previously also apply to bounded loops. In addition, bounded loops require a Loop Start Segment (LS) to appear before the first occurrence and a Loop End Segment (LE) to appear after the last occurrence of the loop. If the loop does not occur, the LS and LE segments are suppressed.

#### **Data Segments in a Transaction Set**

When data segments are combined to form a transaction set, three characteristics are applied to each data segment: a requirement designator, a position in the transaction set, and a maximum occurrence.

#### **Data Segment Requirement Designators**

A data segment, or loop, has one of the following requirement designators for health care and insurance transaction sets, indicating its appearance in the data stream of a transmission. These requirement designators are represented by a single character code.

DESIGNATOR	DESCRIPTION
M- Mandatory	This data segment must be included in the transaction set. (Note that a data
	segment may be mandatory in a loop of data segments, but the loop itself is
	optional if the beginning segment of the loop is designated as optional.)
O- Optional	The presence of this data segment is the option of the sending party.

#### **Data Segment Position**

The ordinal positions of the segments in a transaction set are explicitly specified for that transaction. Subject to the flexibility provided by the optional requirement designators of the segments, this positioning must be maintained.

#### **Data Segment Occurrence**

A data segment may have a maximum occurrence of one, a finite number greater than one, or an unlimited number indicated by ">1."

#### **Functional Group**

A functional group is a group of similar transaction sets that is bounded by a functional group header segment and a functional group trailer segment. The functional identifier defines the group of transactions that may be included within the functional group. The value for the functional group control number in the header and trailer control segments must be identical for any given group. The value for the number of included transaction sets is the total number of transaction sets in the group. See figure A1, Transmission Control Schematic.

#### **Envelopes and Control Structures**

#### **Interchange Control Structures**

Typically, the term "interchange" connotes the ISA/IEA envelope that is transmitted between trading/business partners. Interchange control is achieved through several "control" components. The interchange control number is contained in data element ISA13 of the ISA segment. The identical control number must also occur in data element 02 of the IEA segment. Most commercial translation software products will verify that these two fields are identical. In most translation software products, if these fields are different the interchange will be "suspended" in error.

There are many other features of the ISA segment that are used for control measures. For instance, the ISA segment contains data elements such as authorization information, security information, sender identification, and receiver identification that can be used for control purposes. These data elements are agreed upon by the trading partners prior to transmission and are contained in the written trading partner agreement. The interchange date and time data elements as well as the interchange control number within the ISA segment are used for debugging purposes when there is a problem with the transmission or the interchange. Data Element ISA12, Interchange Control Version Number, indicates the version of the ISA/IEA envelope. The ISA12 does not indicate the version of the transaction set that is being transmitted but rather the envelope that encapsulates the transaction. An Interchange Acknowledgment can be denoted through data element ISA14. The acknowledgment that would be sent in reply to a "yes" condition in data element ISA14 would be the TA1 segment. Data element ISA15, Test Indicator, is used between trading partners to indicate that the transmission is in a "test" or "production" mode. This becomes significant when the production phase of the project is to commence. Data element ISA16, Subelement Separator, is used by the translator for interpretation of composite data elements. The ending component of the interchange or ISA/IEA envelope is the IEA segment. Data element IEA01 indicates the number of functional groups that are included within the interchange. In most commercial translation software products, an aggregate count of functional groups is kept while interpreting the interchange. This count is then verified with data element IEA01. If there is a discrepancy, in most commercial products, the interchange is suspended. The other data element in the IEA segment is IEA02 which is referenced above.

#### **Functional Groups**

Control structures within the functional group envelope include the functional identifier code in GS01. The Functional Identifier Code is used by the commercial translation software during interpretation of the interchange to determine the different transaction sets that may be included within the functional group. If an inappropriate transaction set is contained within the functional group, most commercial translation software will suspend the functional group within the interchange.

The Application Sender's Code in GS02 can be used to identify the sending unit of the transmission. The Application Receiver's Code in GS03 can be used to identify the receiving unit of the transmission.

#### VANTAGE GROUP® 860 Purchase Order Change Request

The functional group contains a creation date (GS04) and creation time (GS05) for the functional group. The Group Control Number is contained in GS06. These data elements (GS04, GS05, AND GS06) can be used for debugging purposes during problem resolution. GS08, Version/Release/Industry Identifier Code is the version/release/sub-release of the transaction sets being transmitted in this functional group. The GS08 does not represent the version of the interchange (ISA/IEA) envelope but rather the version/release/sub-release of the transaction sets that are encompassed within the GS/GE envelope. The Functional Group Control Number in GS06 must be identical to data element 02 of the GE segment. Data element GE01 indicates the number of transaction sets within the functional group. In most commercial translation software products, an aggregate count of the transaction sets is kept while interpreting the functional group. This count is then verified with data element GE01.